


## Small Wall Pack LED

### SWP Small LED Wall Pack Series

Job Name:  
Type:



Dimensions	
Width (D)	8½" (216mm)
Length (B)	7½" (194mm)
Height (A)	9½" (241mm)



#### Features / Specifications:

**Housing:** Die Cast Aluminum Housing, 1/2 inch Coin Plugs with O-rings for Conduit & Photocell on Two Sides & Back, Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating.

**Lens:** Molded Prismatic Borosilicate Glass Lens with Gasket

**Mounting:** Mount Directly Over a 4 inch Recessed Outlet Box, or Use 1/2 inch Surface Conduit or Quick-Mount Bracket.

**Delivered Lumens:** CRI: 80-- 3000K-2636 LUMENS / 4000K-2860 Lumens / Lumens 5000K-2979 Lumens

**Rated Life:** 50,000 Hours 5-Year Warranty Aluminum Boards

**Wattage:** Array: 22.7w, System: 27.6w

**Driver:** Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz; Dimmable Driver

**Listing & Ratings:** CSA Listed for Wet Locations. IP65

**Operating Temperatures:** -40°C to +40°C LM-79 Report Available on Select Models.



## Applications:

Parking areas

Entrances

Walkways

Underpasses

Loading docks

Recreation areas



**Available Options:**

Fill in the boxes with the options you need fax it to us at: 732-833-8085.

NHL-SWP

Wattage:

**23W** 23 Watts

Color Temp:

**30K** =3,000K  
**40K** =4,000K  
**50K** =5,000K

Voltage:

**480** =347-480  
**UNV** =120-277

Wire Guard:

**WG** = Wireguard

Housing Color:

**CC** =Custom Color  
**Z** =Bronze

LED Options:

**DF** =Double Fuse  
**GS** =Glare Shield  
**PC** =Photocell  
**SF** =Single Fuse  
**SP** =Surge Protection